



- (A) S 1°00'00" E 50.00'
- (B) S 89°58' W 40.50'

SURVEY PLAT & LEGAL DESCRIPTION
 APPROVED PER R.C. 315.251
CRB *S 13/101*
 OFFICE OF THE
 GAUGA COUNTY ENGINEER

- 5/8" x 30" rebar set capped "J W Daniel"
- Iron pin found
- 1" iron pin found in monument box

The portion of this map shown as 3.0000 acres was surveyed in accordance with the provisions of chapter 4733-37 of the Ohio Administrative Code.

I hereby certify that I have surveyed the 3.0000 acres shown hereon and that the same is true and correct to the best of my ability.

Jerry W. Daniel
 Jerry W. Daniel P.S. No. 6222



D. and B. Glick
 559 - 107

Map of Survey
 for
 Dan Glick
 Section 3
 Troy Township
 Geauga County, Ohio

J. W. Daniel & Associates, Inc.
 101 North Center Street
 Newton Falls, Ohio 44444
 May, 2001 Job No. 2001-54
 DAT 114

Bearings are to an assumed meridian and are used to denote angles only.

Deed of record: 559 - 107 to D and B. Glick

TRO-00113 TRO 00113

Glick
Pickup 6-1-01
Obsolete

J. W. DANIEL & ASSOCIATES, INC.

4748T.E

SURVEYING & MAPPING

101 NORTH CENTER STREET
NEWTON FALLS, OH 44444
(330) 872-1544

Description of Land
for
Dan Glick

Situated in the Township of Troy, County of Geauga, and State of Ohio, and known as being part of Section 3 in said township, and further bounded and described as follows:

Beginning at a point on the centerline of Nash Road at the northeast corner of land conveyed to A. and L. Miller by deed recorded in Volume 1138, page 1336 of Geauga County Record of Deeds, said point being North 89° 58' 00" East, a distance of 1494.32 feet from a 1" iron pin found at the centerline intersection of said Nash Road and Mumford Road;

thence North 89° 58' 00" East, along said centerline of Nash Road, a distance of 250.00 feet to a point;

thence South 1° 00' 00" East, and passing over a 5/8" capped rebar set at 30.00 feet, a distance of 50.00 feet to a 5/8" capped rebar set;

thence South 89° 58' 00" West, a distance of 40.50 feet to a 5/8" capped rebar set;

thence South 1° 00' 00" East, a distance of 552.12 feet to a 5/8" capped rebar set;

thence South 89° 58' 00" West, a distance of 217.91 feet to a 5/8" capped rebar set on the east line of said Miller's land;

thence North 0° 12' 00" West, along the east line of said Miller's land, and passing over a 5/8" iron pin found at 572.04 feet, a distance of 602.04 feet to a point and the true place of beginning and containing therein 3.0000 acres of land as surveyed in May, 2001 by Jerry W. Daniel, Registered Surveyor No. 6222.

Bearings are to an assumed meridian and are used to denote angles only.
Deed of record: 559 - 107 to D. and B. Glick.

REGISTERED
SURVEYOR
JERRY W. DANIEL
NO. 6222

SURVEY PLAT & LEGAL DESCRIPTION
APPROVED PER R.C. 315.251

CRB 5/31/01

OFFICE OF THE
GEAUGA COUNTY ENGINEER